

## LED Linear Light

 <b>100lm/w, IP65, Dustproof, Anti-corrosion</b> Ceilling surface mounted / hanging each end with wire connection		 <b>100lm/w, IP65, Dustproof, Anti-corrosion</b> Ceilling surface mounted / hanging Meanwell driver		 <b>&gt;120lm/w, IP65, Dustproof, Anti-corrosion</b> Ceilling surface mounted / hanging Can multiple series connection		 <b>100lm/w White/Silver Housing</b> Embedded / hanging Can multiple series connection	
DS-TPL-600-20	20W, 2000lm, 0.6m	DS-TPL-600-20W-2	20W, 2000lm, 0.6m	DS-TPL-600-40W-S	40W, 4800lm, 0.6m	DS-LL-300-15W-3	15W, 1500lm, 0.3m
DS-TPL-900-30W	30W, 3000lm, 0.9m	DS-TPL-900-40W-2	40W, 4000lm, 0.9m	DS-TPL-900-50W-S	50W, 6000lm, 0.9m	DS-LL-600-20W-3	20W, 2000lm, 0.6m
DS-TPL-1200-40W	40W, 4000lm, 1.2m	DS-TPL-1200-60W-2	60W, 6000lm, 1.2m	DS-TPL-1200-60W-S	60W, 7200lm, 1.2m	DS-LL-900-30W-3	30W, 3000lm, 0.9m
DS-TPL-1500-60W	60W, 6000lm, 1.5m	DS-TPL-1500-80W-2	80W, 8000lm, 1.5m	DS-TPL-1500-80W-S	80W, 9600lm, 1.5m	DS-LL-1200-40W-3	40W, 4000lm, 1.2m
 <b>110lm/w White / Silver Housing</b> Ceilling surface mounted / hanging Can multiple series connection		 <b>100lm/w White/Silver Housing</b> Ceilling surface mounted / hanging Can multiple series connection		 <b>100lm/w White/Silver Housing</b> <b>Dimmable &amp; Color temperature adjustable</b> Can multiple series connection		 <b>100lm/w White/Silver Housing</b> <b>Two Side Lighting</b> Can multiple series connection	
DS-LL-900-30W-HB	30W, 3300lm, 0.9m	DS-LL-900-20W-5	20W, 2000lm, 0.9m	DS-LL-900-20W-7	20W, 1800lm, 0.9m	DS-LL-900-30W-6	30W, 2600lm, 0.9m
DS-LL-1200-50W-HB	50W, 5500lm, 1.2m	DS-LL-1200-40W-5	40W, 4000lm, 1.2m	DS-LL-1200-28W-7	28W, 2400lm, 1.2m	DS-LL-1200-50W-6	50W, 4000lm, 1.2m
DS-LL-1500-60W-HB	30W, 6600lm, 1.5m	DS-LL-1500-60W-5	60W, 6000lm, 1.5m	DS-LL-1500-35W-7	35W, 3000lm, 1.5m	DS-LL-1500-70W-6	70W, 6000lm, 1.5m

## LED Panel Light

 <b>Nanometer Material</b> Fan+ Violet LED: 25W LED Panel 40W		 <b>Triac Dimmable / 0-10V Dimmable</b> <b>CCT Adjustable</b> 130lm/w can be provided		 <b>Triac Dimmable / 0-10V Dimmable /</b> <b>CCT Adjustable</b> 130lm/w can be provided		 <b>RGB / RGBW available</b> <b>DC24V</b>	
DS-CL-0606-MPL	65W, 3400lm, AC220-240V/AC110V	DS-0612-72	72W, 7200lm, 1200*600mm,	DS-6262-40	40W, 4000lm, 620*620mm,	DS-0612-48-RGB	48W, 1200*600mm,
<b>Eliminating indoor TVOC concentration</b>		DS-0612-54	54W, 5400lm, 1200*600mm,	DS-0606-54	54W, 5400lm, 600*600mm,	DS-0312-32-RGB	32W, 1200*300mm,
<b>Active, antiseptic and anti-virus</b>		DS-0312-54	54W, 5400lm, 1200*300mm,	DS-0606-48	48W, 4800lm, 600*600mm,	DS-0606-32-RGB	32W, 600*600mm,
<b>Cleaning the air, Reducing air particles</b>		DS-0312-40	40W, 4000lm, 1200*300mm,	DS-0606-40	40W, 4000lm, 600*600mm,	DS-6262-32-RGB	32W, 620*620mm,
 <b>30% Upflight</b> <b>70% Downlight</b> <b>Two Sides Lighting</b>		 <b>AC85-265V</b>		 <b>AC85-265V</b>		 <b>Surface Mounted</b> <b>AC85-265V</b>	
DS-0303-18-S	18W, 1440lm, AC100-240V, 300*300mm,	DS-CL-3W-R20	3W, 250lm, Φ85x20mm, Hole:65mm	DS-CL-3W-S20	3W, 250lm, 85*85x20mm, Hole:65mm	DS-CL-6W-R39	6W, 510lm, Φ120x39mm,
<b>other watts or dimensions are available</b>		DS-CL-6W-R20	6W, 510lm, Φ120x20mm, Hole:110mm	DS-CL-6W-S20	6W, 510lm, 120*120x20mm, Hole:110*110mm	DS-CL-12W-R39	12W, 1100lm, Φ170x39mm,
		DS-CL-9W-R20	9W, 780lm, Φ145x20mm, Hole:135mm	DS-CL-9W-S20	9W, 780lm, 145*145x20mm, Hole:135*135mm	DS-CL-18W-R39	18W, 1650lm, Φ225x39mm,
		DS-CL-12W-R20	12W, 1100lm, Φ175x20mm, Hole:155mm	DS-CL-12W-S20	12W, 1100lm, 175*175x20mm, Hole:155*155mm	DS-CL-24W-R39	24W, 2150lm, Φ300x39mm,
		DS-CL-15W-R20	15W, 1350lm, Φ190x20mm, Hole:175mm	DS-CL-15W-S20	15W, 1350lm, 190*190x20mm, Hole:175*175mm	<b>Square is available</b>	
		DS-CL-18W-R20	18W, 1650lm, Φ225x20mm, Hole:205mm	DS-CL-18W-S20	18W, 1650lm, 225*225x20mm, Hole:205mm		
		DS-CL-24W-R20	24W, 2150lm, Φ300x20mm, Hole:280mm	DS-CL-24W-S20	24W, 2150lm, 300*300x20mm, Hole:280mm		

## LED Track Light

E27 base	3-5 years warranty	Color Temperature : 3000K / 4000K / 6000K;	Isolated Driver	AC110-240V			
							
<b>CRI 80-97Ra</b> <b>White/Black Housing</b> 15° / 24° / 38° / 60° <b>100lm/w ; 130lm/w</b> With Clamp Removable / Surface mounted		<b>CRI 80-97Ra</b> <b>White/Black Housing</b> 15° / 24° / 38° / 60° <b>110-120lm/w</b> Tridonic Driver+ Citizen COB LED		<b>CRI 80-97Ra</b> <b>White/Black Housing</b> 15° / 24° / 38° / 60° <b>110-120lm/w</b> Tridonic Driver+ Citizen COB LED		<b>CRI 80-95Ra</b> <b>2wires, 3wires, 4wires</b> Beam Angle:20°/30°/40°/60° <b>100lm/w</b> White/Black/Silver Housing <b>130lm/w</b>	
<b>DS-RL15W-COB-8</b>	15W, 2450lm / 3200lm	<b>DS-RL15W-COB-8L</b>	15W, 1650-1800lm	<b>DS-RL40W-COB-8L</b>	40W, 4400-4800lm	<b>DS-RL20W-COB-4</b>	20W,2300lm / 2600lm
<b>DS-RL25W-COB-8</b>	25W, 2450lm / 3200lm	<b>DS-RL25W-COB-8L</b>	25W, 2750-3250lm	<b>DS-RL45W-COB-8L</b>	45W, 4950-5400lm	<b>DS-RL30W-COB-4</b>	30W,3300lm / 3900lm
<b>DS-RL30W-COB-8</b>	30W, 2900lm / 3800lm	<b>DS-RL30W-COB-8L</b>	30W, 3300-3600lm	<b>DS-RL50W-COB-8L</b>	50W, 5500-6000lm	<b>DS-RL40W-COB-4</b>	40W,4500lm / 5000lm

## LED Down Light

Epistar LED	UGR<19; SDCM:<4	AC200-240V	Color Temperature : 3000K / 4000K / 6000K;	Dimmable available	IP44	3 years warranty	
							
White/Inner ring brushed Golden/chrome Inner ring and surface ring brushed Nickel		<b>100-110lm/w</b> <b>Anti-glare URG 3-7</b> 30°/40°/60° <b>LIFUD/BOKE driver</b>		<b>100-110lm/w</b> <b>Anti-glare URG 3-7</b> 30°/40°/60° <b>LIFUD/BOKE driver</b>		<b>110-120lm/w</b> <b>Osram/Philip 3030</b> 120° <b>LIFUD/BOKE driver</b>	
<b>DS-CL-5W</b>	5W, 450lm, D85*H27mm, Φ75mm(hole) / <b>68mm</b>	<b>DS-CL-7W-5</b>	7W, 700-800lm, D96*H68mm HoleΦ75-86mm	<b>DS-CL-30W-5</b>	30W 3000-3200lm, D 170*H120mm, Φ140-155mm(hole)	<b>DS-CL-12W-2</b>	12W,1350-1400lm, D110mm*H54mm, Φ95mm(hole)
<b>DS-CL-8W</b>	8W, 720lm, D85*H27mm, Φ75mm(hole) / <b>68mm</b>	<b>DS-CL-10W-5</b>	10W,1000-1200lm, D96*H80mm, Hole Φ75-86mm	<b>DS-CL-40W-5</b>	40W 4000-4200lm, D200*H130mm, Φ160-180mm(hole)	<b>DS-CL-20W-2</b>	20W,2200-2400lm, D145mm*H70mm, Φ125mm(hole)
<b>IP44 / IP65</b>		<b>DS-CL-16W-5</b>	16W,,1600-1700lm D120*H102mm, Φ95-108mm(hole)	<b>DS-CL-50W-5</b>	50W 5000-5400lm, D250*H126mm, Φ205-228mm(hole)	<b>DS-CL-30W-2</b>	30W,3300-3600lm, D190mm*H87mm, Φ165mm(hole)
<b>0-10V Dimmable, Dali Dimmable, Dim to Warm dimmable</b>		<b>DS-CL-20W-5</b>	20W 2000-2100lm, D145*H105mm Φ118-132mm(hole)			<b>DS-CL-50W-2</b>	50W 5500-6000lm, D230mm*H100mm, Φ200mm(hole)
							
<b>100lm/w</b> <b>Epistar COB LED /</b> Beam Angle:60° <b>SMD5630 LED</b>		<b>100-110lm/w</b> 20°/30°/40°/60° <b>LIFUD/BOKE driver</b>		<b>IP65 Waterproof</b> Beam Angle: <b>90.120°</b>		<b>100-110lm/w</b> 20°/30°/40° <b>LIFUD driver</b> White/Silver/Black housing	
<b>DS-CL-7W-1</b>	9W, 630-700lm,D110mm*H50mm, Φ95mm(hole)	<b>DS-CL-10W-G</b>	10W, 1000-1100lm, D87*H55 Φ75mm(hole)	<b>DS-CL-5W-W</b>	5W, 420lm D90*45mm, Φ75mm	<b>DS-CL-10W-M</b>	10W 1000-1100lm D75*H130mm
<b>DS-CL-12W-1</b>	12W, 1100-1200lm, D135mm*H50mm,Φ115mm(hole)	<b>DS-CL-20W-G</b>	20W,2000-2300lm, D130*H70mm Φ115mm(hole)	<b>DS-CL-7W-W</b>	9W, 780lm D90*45mm, Φ75mm	<b>DS-CL-20W-M</b>	20W2000-2200lm D100*H130mm
<b>DS-CL-20W-1</b>	20W, 1800-1900lm, D190mm*H60mm, Φ170mm(hole)	<b>DS-CL-30W-G</b>	30W, 3000-3300lm D165*H130mm Φ150mm(hole)	<b>DS-CL-12W-W</b>	12W,1080lm,D108*50mm, Φ95mm	<b>DS-CL-30W-M</b>	30W 3000-3300lm D100*H165mm
<b>DS-CL-30W-1</b>	20W,2800-2900lm, D220mm*H60mm, Φ200mm(hole)	<b>DS-CL-50W-G</b>	50W, 5000-5500lm, D200*H165mm, Φ185mm(hole)	<b>DS-CL-15W-W</b>	15W,1250lm, D108*50mm, Φ95mm	<b>DS-CL-40W-M</b>	40W 4000-4400lm D158*H180mm

## LED Flexible Strip Light

							
<b>Aluminum Profiles</b>		DC24V	<b>5730/Samsung 5630</b>	DC12V/24V/48V	<b>SMD 5050</b>	DC12V/24V,	<b>SMD 3014 Sideview</b>
<b>Multiple sizes, multiple shapes can be selected</b>		IP20	WW/W	IP20/IP65/IP68		IP20 / IP68	WW/NW/W/R/G/B/Y
		<b>DS-FL-5730-60</b>	60pcs/m, 1800lm, 19w/m,	<b>DS-FL-5050-30</b>	30pcs/m, 7.2w/m,	<b>DS-FL-3014-60SV</b>	60pcs/m,
		<b>DS-FL-5730-120</b>	120pcs/m, 3600lm, 36w/m	<b>DS-FL-5050-60</b>	60pcs/m, 14.4w/m,	<b>DS-FL-3014-120SV</b>	120pcs/m,
							
DC24V	<b>SMD 2835</b>	DC12V/24V	<b>SMD 5050 RGBW</b>	DC24V	<b>SMD 2216 Bi-Color WW-CW</b>	DC12V/24V	<b>SMD 3528</b>
IP20/IP65/IP68	WW/NW/W/R/G/B/Y	IP20/IP65	<b>RGBW in one LEDs</b>	IP20/IP65/IP68	WW/NW/W	IP20/IP65/IP68	WW/NW/W/R/G/B/Y
<b>DS-FL-2835-60</b>	60pcs/m, 13w/m,	<b>DS-FL-5050- RGBW-60</b>	60pcs/m, 17w/m,	<b>DS-FL-2216-240</b>	240pcs/m, 17w/m,	<b>DS-FL-3528-60</b>	60pcs/m, 4.8w/m,
<b>DS-FL-2835-84</b>	84pcs/m, 17w/m,	<b>DS-FL-5050- RGBW-72</b>	72pcs/m, 7w/m,	<b>DS-FL-2216-280</b>	280pcs/m, 17.5w/m	<b>DS-FL-3528-120</b>	60pcs/m, 9.6w/m,
<b>DS-FL-2835-120</b>	120pcs/m, 25w/m,	<b>DS-FL-5050- RGBW-84</b>	84pcs/m, 24.2w/m,	<b>DS-FL-2216-312</b>	312pcs/m, 23w/m	<b>DS-FL-3528-240</b>	240pcs/m, 17w/m
<b>DS-FL-2835-168</b>	168pcs/m, 35w/m,	<b>DS-FL-5050- RGBW-96</b>	60pcs/m, 27.6w/m,	<b>DS-FL-2216-560</b>	560pcs/m, 34.5w/m		

## LED Outdoor Light

							
<b>130lm/w Philips LED and Driver</b>		<b>130lm/w Philips LED and Driver</b>		<b>110-120lm/w PHILIPS LED + Meanwell</b>		<b>130lm/w Philips LED and Driver</b>	
<b>RGB / PIR can be provided</b>							
<b>DS-FL-10W-5</b>	10W, 1200lm	<b>DS-FL-100W-5</b>	200W, 14000lm	<b>DS-HB100-5</b>	100W, 12000lm, D285*H165mm	<b>DS-TNL-100W</b>	100W, 13000lm
<b>DS-FL-20W-5</b>	20W, 2600lm	<b>DS-FL-150W-5</b>	200W, 21000lm	<b>DS-HB120-5</b>	120W, 14500lm, D320*H180mm	<b>DS-TNL-200W</b>	200W, 26000lm
<b>DS-FL-30W-5</b>	30W, 39000lm	<b>DS-FL-200W-5</b>	200W, 28000lm	<b>DS-HB150-5</b>	150W, 18000lm, D320*H180mm	<b>DS-TNL-300W</b>	300W, 39000lm
<b>DS-FL-50W-5</b>	50W, 65000lm			<b>DS-HB200-5</b>	200W, 24000lm, D400*H208mm	<b>DS-TNL-400W</b>	400W, 52000lm
				<b>DS-HB240-5</b>	240W, 28500lm, D400*H208mm	<b>DS-TNL-500W</b>	500W, 65000lm
							
<b>110lm/w Samsung LED+Meanwell</b>		<b>Integrated LED solar street Light</b>		<b>E27 / E40, 360° Beam Angle</b>		<b>E27 / E40 360° Beam Angle</b>	
<b>DS-STL-50W</b>	500W, 5000lm	<b>DS-STL-15W-S</b>	12V / 15W 1500-1650lm	<b>DS-BL-27W-C-3</b>	27W, 2500lm, Φ93xH197mm	<b>DS-BL-60W-C-4</b>	60W, 5400lm, Φ93xH285mm
<b>DS-STL-100W</b>	100W, 10000lm	<b>DS-STL-20W-S</b>	12V / 20W 2000-2200lm	<b>DS-BL-36W-C-3</b>	36W, 3300lm, Φ93xH233mm	<b>DS-BL-80W-C-4</b>	80W, 6800lm, Φ120xH290mm
<b>DS-STL-150W</b>	150W, 15000lm	<b>DS-STL-40W-S</b>	12V / 40W 4000-4400lm	<b>DS-BL-45W-C-3</b>	45W, 4100lm, Φ93xH248mm	<b>DS-BL-100W-C-4</b>	100W, 8500lm, Φ120xH308mm
<b>DS-STL-200W</b>	200W, 20000lm	<b>DS-STL-60W-S</b>	12V / 60W 6000-6600lm	<b>DS-BL-54W-C-3</b>	54W, 4900lm, Φ93xH276mm	<b>DS-BL-120W-C-4</b>	120W, 10200lm, Φ120xH345mm
<b>DS-STL-250W</b>	250W, 25000lm						
<b>DS-STL-300W</b>	300W, 30000lm	<b>DS-STL-80W-S</b>	12V / 80W 8000-8800lm				